


# MB422 PCB Terminal Block, Modular



MB

DIMENSIONS/POSITIONS		MB422-750MA	MB422-762MA
間距	Pitch	7.50mm	7.62mm
位數	Poles	2 ~ 3Poles	2 ~ 3Poles
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated	Brass, Ni Plated
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	12 ~ 24AWG	12 ~ 24AWG
剝線長度	Wire Strip Length	8mm	8mm
PCB孔徑	PCB Hole Diameter	1.5mm	1.5mm
最大緊固扭矩	Tightening Torque, Max.	5.0 Lb-in	5.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

連接符合標準	Connection in acc. with standard EN-VDE		
額定電流 $I_n$	Nominal Current $I_n$	25A	25A
額定橫截面	Nominal Cross Section	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>
最大負載電流	Maximum load current	25A	25A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓,UL/CUL	Nominal voltage, UL/CUL	300V	300V
額定電流,UL/CUL	Nominal current, UL/CUL	25A	25A

