


# MD024 Connector, Header



MD

### DIMENSIONS/POSITIONS

### MD024-350

|        |                       |                   |
|--------|-----------------------|-------------------|
| 間距     | Pitch                 | 3.50mm            |
| 位數     | Poles                 | 2 ~ 24Poles       |
| 塑膠本體   | Housing Material      | PA 66             |
| 焊針     | Pin Dimensions        | Brass, Tin Plated |
| PCB孔徑  | PCB Hole Diameter     | 1.5mm             |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C   |

### TECHNICAL DATA

|   |  |      |
|---|--|------|
| 連接符合標準<br>Connection in acc. with standard EN-VDE     |  |      |
| 額定電流 I <sub>n</sub><br>Nominal Current I <sub>n</sub> |  | 10A  |
| 額定橫截面<br>Nominal Cross Section                        |  | -    |
| 最大負載電流<br>Maximum load current                        |  | 10A  |
| 絕緣材料<br>Insulating Material                           |  | PA   |
| 阻燃等級,符合UL94<br>Inflammability class acc. to UL94      |  | V0   |
| 額定電壓,UL/CUL<br>Nominal voltage, UL/CUL                |  | 300V |
| 額定電流,UL/CUL<br>Nominal current, UL/CUL                |  | 10A  |

