




CDU 4/3N



CDU 4/4N



CDU 6N



Specifications (產品規格)	4 mm ²	4 mm ²	6 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	300V/30A/AWG 10-24	300V/30A/AWG 10-24	600 V / 50 A / AWG 8-26
CSA	300V/30A/AWG 10-24	300V/30A/AWG 10-24	600 V / 50 A / AWG 8-26
IEC	500V/32A/0.2-4mm ²	500V/32A/0.2-4mm ²	800V/57A/0.5-6mm ²
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3	8KV / 3	8KV / 3
Torque (lb-in) (扭緊力矩)	7	7	14
Clamping Screw (M) (螺絲)	M3	M3	M4
Insulation stripping length(mm) (剝線長度)	8 mm	8 mm	10-12 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	6.2/50.5/47	6.2/63.5/47	8 x 42.5 x 47
For TS35x15	6.2/50.5/54.5	6.2/63.5/54.5	8 x 42.5 x 54.5
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	CEW35/2 50 SEW35 50	CEW35/2 50 SEW35 50	SEW35 50 CEW35/2 50
End Plate (擋板)	CDU4/3-C 50	CDU4/4-C 50	CEP 6 50
Partition (擋板/隔片)	- 50	- 50	CEP 6 50
Cross Jumper (中心式聯接件)	50	50	CQV 6/2 50
	CQVM4/2 50	CQVM4/2 50	CQV 6/3 50
	50	50	CQV 6/4 50
	20	20	CQV 6/10 20
Comb Link (邊接式聯接件)	50	50	CQB-6/2 50
	CQB4/2 50	CQB4/2 50	CQB-6/3 50
	20	20	CQB-6/10 20
Warning Cover (安全標示蓋)	- 50	- 50	WSS6 50
Marking Tags (標記號)	W6 500	W6 500	W6 W6Z W6K 500
Test plug (測試插頭)	- 20	- 20	TPS2.3 (Ø2.3) 20 TPS4 (Ø4) 20
Socket (測試插孔)	- 50	- 50	TP2.3 50 TP4 50
Protection Cover (防觸蓋)	- 20	- 20	DP1 20
Retaining Plates (中界板)	- 50	- 50	AD1 50
Tool (工具)	DS3	DS3	DS4