



CDU 10N



CDU 2.5M



CDU 4M



Specifications (產品規格)	10 mm ²	2.5 mm ²	4 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	600 V/65 A/AWG 6-24	300V/20A/AWG 12-22	300V/30A/AWG 10-22
CSA	600 V/65 A/AWG 6-24	300V/20A/AWG 12-22	300V/30A/AWG 10-22
IEC	800V/76A/0.5-10mm ²	400V/24A/0.2-2.5mm ²	500V/30/0.5-4mm ²
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3	6KV / 3	6KV / 3
Torque (lb-in) (扭緊力矩)	19	7	7.7
Clamping Screw (M) (螺絲)	M4	M2.6	M3
Insulation stripping length(mm) (剝線長度)	10-12 mm	6 mm	6mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	10 x 42.5 x 47		
For TS15x5.5	10 x 42.5 x 54.5	5x 28 x 33	6x 28 x 33
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50 CEW35/2 50	CEW 15 50	CEW 15 50
End Plate (擋板)	CEP 6 50	CEP 7 50	CEP 7 50
Partition (擋板/隔片)	CEP 6 50		
Cross Jumper (中心式聯接件)	CQV 10/2 50	CQVM 2.5/2 50	CQVM 4/2 50
	CQV 10/3 50	CQVM 2.5/3 50	CQVM 4/3 50
	CQV 10/4 50	CQVM 2.5/10 50	CQVM 4/10 50
	CQV 10/10 20		
	CQB-10/2 50		
Comb Link (邊接式聯接件)	CQB-10/3 50	CQB 2.5/2 50	CQB 4/2 50
	CQB-10/10 20	CQB 2.5/3 50	CQB 4/3 50
Warning Cover (安全標示蓋)	WSS 10 50		
Marking Tags (標記號)	W6 W6Z W6K 500	W5 W5Z W5K 500	W6 W6Z W6K 500
Test plug (測試插頭)	TPS2.3 (Ø2.3) 20		
	TPS4 (Ø4) 20		
Socket (測試插孔)	TP2.3 50		
	TP4 50		
Protection Cover (防觸蓋)	DP1 20		
Retaining Plates (中界板)	AD1 50		
Tool (工具)	DS4	DS3	DS3