





CPE 4N



CPE 4/3N



CPE 6N



Specifications (產品規格)	4 mm ²		4 mm ²		6 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	AWG 10-26		AWG 10-24		AWG 8-26	
CSA	AWG 10-26		AWG 10-24		AWG 8-26	
IEC	0.2-4mm ²		0.2-4mm ²		0.2-6mm ²	
Insulating impulse voltage withstand /Pollution degree (額定衝擊電壓 /污染等級)	8KV / 3		6KV / 3		8KV / 3	
Torque (lb-in) (扭緊力矩)	8.5		8		16	
Clamping Screw (M) (螺絲)	M3		M3		M4	
Insulation stripping length(mm) (剝線長度)	10-14 mm		8 mm		12-16 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	6 x 42.5 x 47.5		6.2x50.5x47		8 x 42.5 x 47.5	
For TS35x15	6 x 57 x 55		6.2x50.5x54.5		8 x 57 x 55	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	CEW35/2	50	SEW35	50
	CEW35/2	50	SEW35	50	CEW35/2	50
Comb Link (邊接式聯接件)	CQB 4/2	50		50	CQB 6/2	50
	CQB 4/3	50	CQB4/2	50	CQB 6/3	50
	CQB 4/10	20		20	CQB 6/10	20
MarkingTags (標記號)	W6 W6Z W6K	500	W6 W6Z W6K	500	W6 W6Z W6K	500
	W8 W8Z W8K	400			W8 W8Z W8K	400
Protection Cover (防觸蓋)	DP1	20			DP1	20
Retaining Plates (中界板)	AD1	50			AD1	50
Tool (工具)	DS3		DS3		DS4	