



### SDU 4/3



### SDU 4/4



### SDU 6



Specifications (產品規格)	4 mm <sup>2</sup>	4 mm <sup>2</sup>	6 mm <sup>2</sup>
<b>Technical Data (技術參數)</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>
UL	c  US 600V/20A/AWG 12-28	c  US 600V/20A/AWG 12-28	c  US 600V/30A/AWG 10-24
CSA	600V/20A/AWG 12-28	600V/20A/AWG 12-28	600V/30A/AWG 10-24
IEC	800V/32A/0.2~4mm <sup>2</sup>	800V/32A/0.2~4mm <sup>2</sup>	800V/41A/0.2~6mm <sup>2</sup>
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	8-9 mm	9-10 mm	12-13 mm
Material/Available Color (材質顏色)			
<b>Rail Dimensions (導軌尺寸)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>
For TS35x7.5	6 x 73.5 x 36.5	6 x 86 x 36.5	8 x 74.5 x 40
For TS35x15	6 x 73.5 x 44	6 x 86 x 44	8 x 74.5 x 47.5
<b>Accessories (附件)</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>
End Bracket (終端擋板)	SEW35    50	SEW35    50	SEW35    50
End Plate (擋板)	SEP 5    50	SEP 6    50	SEP 7    50
Comb Link (連接式聯接件)	SQV 4/2    50	SQV 4/2    50	SQV 6/2    50
	SQV 4/3    50	SQV 4/3    50	SQV 6/3    50
MarkingTags (標記號)	W6 W6Z W6K    500	W6 W6Z W6K    500	W6 W6Z W6K    500
Tool (工具)	DS3	DS3	DS4