


## Features of Spring Clamp Terminal Blocks



SDU 16










### Features of Spring Clamp Terminal Blocks

- Space - saving design / Front connection.
- Vibration proof anti-loosening wire connection with pre-stressed Spring Clamp.
- Easy to operate, fast wiring installation with top wire entry.
- Easy mounting and dismounting from the terminal rail.
- Corrosion - proof terminal points.
- Low contact resistance.
- Easy for the extension of terminal connection.
- Easy handling and safe connection.

### 彈片壓接型接線座之特性

- 節省空間之設計 / 前緣導線連接方式
- 高強度壓力的彈片迫緊連接方式，具有抗震與防鬆的效果
- 操作簡便且快速的導線安裝方式 ( 頂部進線 )
- 抗腐蝕性佳 ( 使用良好的金屬材料 )
- 接線座從軌道上安裝及拆卸容易
- 低接觸電阻
- 容易擴充及延伸性佳
- 操作簡便且連結處安全性高

Specifications (產品規格)	16 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	
UL	cUL <sup>us</sup> 600V/65A/AWG 4-16	
CSA	600V/65A/AWG 4-16	
IEC	800V/85A/1.5-16 mm <sup>2</sup>	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3	
Insulation stripping length(mm) (剝線長度)	16-17mm	
Material/Available Color (材質顏色)		
Rail Dimensions (導軌尺寸)	T / W / H (mm)	
For TS35x7.5 	12.2x82.5x51	
For TS35x15 	12.2x82.5x58.5	
Accessories (附件)	Cat. No.	Qty.
End Bracket (終端擋板) 	SEW35	50
End Plate (擋板) 	SEP12	50
Comb Link (邊接式聯接件) 	SQV16/2	50
Marking Tags (標記號) 	W6 W6Z W6K	500
Tool (工具) 	DS5	