



### SDUNP 2.5/2



### SDUNT 2.5



### SDUNT 2.5/2



Specifications (產品規格)	2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	600V/15A/AWG 12-28		cUL <sup>®</sup> 600V/15A/AWG 12-28		600V/15A/AWG 12-28	
CSA	600V/15A/AWG 12-28		600V/15A/AWG 12-28		600V/15A/AWG 12-28	
IEC	800V/24A/0.2-2.5 mm <sup>2</sup>		800V/24A/0.2-2.5 mm <sup>2</sup>		800V/24A/0.2-2.5 mm <sup>2</sup>	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree 污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	10-12mm		10-12mm		10-12mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5			6x37x32		10x37x32	
For TS35x15			6x37x39.5		10x37x39.5	
For TS15x5.5	10x32.2x30					
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW15	50	SEW35	50	SEW35	50
End Plate (擋板)	SDUNB2.5-C	50	SDUNB2.5-C	50	SDUNB2.5-C	50
Comb Link (連接式聯接件)						
Marking Tags (標記號)	W5 W5Z W5K	500	W6 W6Z W6K	500	W5 W5Z W5K	500
Tool (工具)	DS3		DS3		DS3	