








SDUS 4

SDUS 4/2



Specifications (產品規格)	4 mm ²		4 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	c us 300V/20A/AWG28-12		c us 300V/20A/AWG28-12	
CSA	300V/20A/AWG28-12		300V/20A/AWG28-12	
IEC	630V/24A/0.2-4mm ²		630V/24A/0.2-4mm ²	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	9-10mm		9-10mm	
Material/Available Color (材質顏色)				
Dimensions (外形尺寸)	T / W / H (mm)		T / W / H (mm)	
	7x33.4x23		12x33.4x23	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.
 Central Terminals (中間端子)	SDUB 4-B	25	SDUB 4-B	25
	SDUB 4/2-B	25	SDUB 4/2-B	25
 End Bracket (擋板)	SDUB 4-C	25	SDUB 4-C	25
 Comb Link (邊接式聯接件)	SQB 4	25	SQB 4	25
 Lever (壓板)	SDUB 4-D	25	SDUB 4-D	25
 Tool (工具)	DS 3	10	DS 3	10