



## Features of Spring Clamp Ground Terminal Blocks 彈片接地型接線座





DST 1.5/3-PE-D



DST 1.5/4-PE-D



DST 2.5-PE-D

Specifications (產品規格)	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>
<b>Technical Data (技術參數)</b>	<b>Rated voltage / Rated current / Wire Size</b>	<b>Rated voltage / Rated current / Wire Size</b>	<b>Rated voltage / Rated current / Wire Size</b>
<b>UL</b>	600V / AWG 28-14	600V / AWG 28-14	600V / AWG 28-12
<b>CSA</b>	600V / AWG 28-14	600V / AWG 28-14	600V / AWG 28-12
<b>IEC</b>	500V / 0.08-1.5mm <sup>2</sup>	500V / 0.08-1.5mm <sup>2</sup>	500V / 0.08-2.5mm <sup>2</sup>
<b>Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 汙染等級)</b>	6KV / 3	6KV / 3	8KV / 3
<b>Insulation stripping length (mm) (剝線長度)</b>	10mm	10mm	10mm
<b>Material / Available Color (材質顏色)</b>			
<b>Rail Dimensions (導軌尺寸)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>
For TS35x 7.5	4.2 x 60.7 x 36.5	4.2 x 72.6 x 36.5	5.2 x 48.8 x 36.5
For TS35x 15	4.2 x 60.7 x 44	4.2 x 72.6 x 44	5.2 x 48.8 x 44
<b>Accessories (附件)</b>	<b>Cat. No. Qty.</b>	<b>Cat. No. Qty.</b>	<b>Cat. No. Qty.</b>
<b>End Bracket (終端擋板)</b>	SEW35 50	SEW35 50	SEW35 50
<b>End Plate (擋板)</b>	DD-ST2.5/3-DP 50	DD-ST2.5/4-DP 50	DD-ST2.5-DP 50
<b>Comb Link (選接式聯接件)</b>	ODFBS2-4 50 ODFBS3-4 50 ODFBS4-4 50 ODFBS5-4 50 ODFBS10-4 10	ODFBS2-4 50 ODFBS3-4 50 ODFBS4-4 50 ODFBS5-4 50 ODFBS10-4 10	ODFBS2-5 50 ODFBS3-5 50 ODFBS4-5 50 ODFBS5-5 50 ODFBS10-5 10
<b>Marking Tags (標記號)</b>	DUC-TMF4 10 (側面 120 位) DUC-TM4 10 (正面 120 位)	DUC-TMF4 10 (側面 120 位) DUC-TM4 10 (正面 120 位)	DUC-TMF5 10 (側面 96 位) DUC-TM5 10 (正面 96 位)
<b>Tool (工具)</b>	DS2 (0.4 x 2.5mm)	DS2 (0.4 x 2.5mm)	DS3 (0.4 x 3.5mm)